

MOTIP Industrial Chain Grease

Ord.-no.: 090205, 290205

Technical Information



Lubricate chain-driven transmissions which are subjected to heavy loads with MOTIP Industrial Chain Grease. Industrial chain grease can be processed like oil, with the properties of grease.

Quality & properties

- To be processed like oil, with the properties of grease
- Outstanding mechanical and thermal stability
- Prevents wear and sticking
- Dilatant
- Water-repellent
- Good adhesion
- Resistant to weather influences
- Directed jetspray
- Resistant to weak acids and bases

Physical & chemical data

- Base: Synthetic oil
- Colourname:
 - ◊ no colour
 - ◊ transparent
- Smell: Characteristic
- Surfaces: Chains, Chain driven transmissions (liable to heavy load), Conveyors
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Spray rate: 2,9
- Vapour pressure: 3500/20 bar
- Relative density: 0.844 g/ml
- Storage stability: 10 y
- Content:
 - ◊ 500 ML
 - ◊ 200 ML

How to use

- Before use, carefully read the directions on the packaging and act accordingly.
- The aerosol should have room temperature
- Best processing temperature 10 to 25°C.
- Before use, shake the aerosol.
- Apply industrial chain grease in a thin layer.
- During the initial flow phase, when the spray can really penetrate the treated chain, the spray has a foaming effect.
- Optimum lubrication is obtained after evaporation of the solvent.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labeling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

For any further technical questions call our hotline +31 (0) 561 69 44 00 from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

As of June 10, 2022 – This release replaces all eventually earlier issued versions.

