

Page 1/10

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 22.02.2024 Version number 2 (replaces version 1) Revision: 30.03.2022

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: MOTIP POWER BRAKE CLEANER 500 ML
- · Article number: 090563
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

· Process category

PROC7 Industrial spraying

PROC11 Non industrial spraying

- · Application of the substance / the mixture Cleaning agent/ Cleaner
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

European Aerosols B.V.\*

Wolfraamweg 2

NL-8471 XC Wolvega

The Netherlands

Tel: +31 (0)561 694400

e-mail: sds-nl@european-aerosols.com

- \*Formerly known as Motip Dupli B.V.
- · Further information obtainable from: Department Product Safety
- · 1.4 Emergency telephone number:
  - +31 (0)561-694400 (09:00h 17:00h)

UK: NPIS National Poisons Information Centre Tel: +44 0344 892 0111

## SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



• environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

(Contd. on page 2)

Version number 2 (replaces version 1) Revision: 30.03.2022 Printing date 22.02.2024

Trade name: MOTIP POWER BRAKE CLEANER 500 ML

(Contd. of page 1)

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms







GHS02

GHS07 GHS09

- · Signal word Danger
- · Hazard-determining components of labelling:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe spray.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents / container in accordance with regional regulations.

· Additional information:

Buildup of explosive mixtures possible without sufficient ventilation.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

## SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
EC number: 921-024-6	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-	<i>75-≤100%</i>
Reg.nr.: 01-2119475514-35	hexane	
	<ul><li>Flam. Liq. 2, H225</li><li>Asp. Tox. 1, H304</li></ul>	
	🕸 Aquatic Chronic 2, H411	
	🄖 Skin Irrit. 2, H315; STOT SE 3, H336	
CAS: 124-38-9	carbon dioxide	2.5-<5%
EINECS: 204-696-9	🔷 Press. Gas (Liq.), H280	

· Additional information:

The content of Benzene (EINECS-Nr. 200-753-7) in the ingredients is less than 0,1% (Note P Annex 1A 1272/2008 EU), so the classification as carcinogen need not to apply.

For the wording of the listed hazard phrases refer to section 16.

Printing date 22.02.2024 Version number 2 (replaces version 1) Revision: 30.03.2022

Trade name: MOTIP POWER BRAKE CLEANER 500 ML

(Contd. of page 2)

## SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- · 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· 5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · 5.3 Advice for firefighters -
- · Protective equipment: Mouth respiratory protective device.

## SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources.

· 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

# SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- · Information about fire and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Keep respiratory protective device available.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.

(Contd. on page 4)

Printing date 22.02.2024 Version number 2 (replaces version 1) Revision: 30.03.2022

Trade name: MOTIP POWER BRAKE CLEANER 500 ML

(Contd. of page 3)

· Storage class: 2 B

 $\cdot$  7.3 *Specific end use(s) No further relevant information available.* 

## SECTION 8: Exposure controls/personal protection

### · 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

#### 124-38-9 carbon dioxide

WEL Short-term value: 27400 mg/m³, 15000 ppm Long-term value: 9150 mg/m³, 5000 ppm

#### · DNELs

#### Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Oral	DNEL	699 mg/kg (Consumer, longterm systemic)
Dermal	DNEL	773 mg/kg (Worker, longterm systemic)
	DNEL	699 mg/kg (Consumer, longterm systemic)
Inhalative	DNEL	2035 mg/m3 (Worker, longterm systemic)
	DNEL	608 mg/m3 (Consumer, longterm systemic)

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A2/P3

· Hand protection



Protective gloves

# · Material of gloves

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

### · Penetration time of glove material

Butyl rubber gloves with a thickness of 0.4 mm are resistant to:

Acetone: 480 min Butyl acetate: 60 min Ethyl acetate: 170 min Xylene: 42 min

Butyl rubber gloves with a thickness of 0.4 mm are solvent resistant for 42-480 minutes. As protective measure, we recommend that users and responsible persons for work safety assume solvent resistance length of 42 minutes. Considering the data in section 3 of this SDS, one can assume longer resistance length in particular cases.

(Contd. on page 5)

Printing date 22.02.2024 Version number 2 (replaces version 1) Revision: 30.03.2022

Trade name: MOTIP POWER BRAKE CLEANER 500 ML

(Contd. of page 4)

· Eye/face protection Not required.

# SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

Physical state
Colour:
Odour:
Odour threshold:
Melting point/freezing point:

Aerosol
Clear
Solvent-like
Not determined.
<-25 °C (<-13 °F)</p>

· Boiling point or initial boiling point and boiling

range Not applicable, as aerosol.

· Flammability Not applicable.

· Lower and upper explosion limit

· Lower: 0.6 Vol % (Hydrocarbons, C6-C7, n-alkanes,

isoalkanes, cyclics, <5% n-hexane)

· Upper: 8 Vol % (Hydrocarbons, C6-C7, n-alkanes, isoalkanes,

cyclics, <5% n-hexane)

• Flash point: -12 °C (10.4 °F) (Hydrocarbons, C6-C7, n-alkanes,

isoalkanes, cyclics, <5% n-hexane)

Not applicable, as aerosol.

· Auto-ignition temperature: >200 °C (>392 °F) (Hydrocarbons, C6-C7, n-alkanes,

isoalkanes, cyclics, <5% n-hexane)

· Decomposition temperature: Not determined.

 $\cdot pH$  Mixture is non-soluble (in water).

· Viscosity:

Kinematic viscosity
 Dynamic:
 Not determined.
 Not determined.

· Solubility

• water: Not miscible or difficult to mix.

· Partition coefficient n-octanol/water (log value) Not determined.

• Vapour pressure at 20 °C (68 °F): 5500 hPa (4125.3 mm Hg)

· Density and/or relative density

Density at 20 °C (68 °F):
 Relative density
 Vapour density
 Not determined.
 Not determined.

· 9.2 Other information

· Appearance:

· Form: Aerosol

· Important information on protection of health and

environment, and on safety.

• Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

· Solvent content:

• Organic solvents: 97.0 %
• VOC (EC) ---

710.0 g/l 97.00 %

• VOC-EU%
 • Solids content:
 97.00 %
 0.0 %

· Change in condition

• Evaporation rate Not applicable.

· Information with regard to physical hazard classes

· Explosives Void

(Contd. on page 6)

Printing date 22.02.2024 Version number 2 (replaces version 1) Revision: 30.03.2022

Trade name: MOTIP POWER BRAKE CLEANER 500 ML

	(Contd. of page 5
· Flammable gases	Void
· Aerosols	Extremely flammable aerosol. Pressurised container:
	May burst if heated.
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flamme	able
gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

# SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

# SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values relevant for classification:

## Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Oral	LD50	>5840 mg/kg (rat)
Dermal	LD50	>2920 mg/kg (rab)
Inhalative	LC50 / 4h	>25.2 mg/l (rat)

- · Skin corrosion/irritation Causes skin irritation.
- · Serious eye damage/irritation No irritating effect.
- · Respiratory or skin sensitisation No sensitising effects known.
- · STOT-single exposure May cause drowsiness or dizziness.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

GB

Printing date 22.02.2024 Version number 2 (replaces version 1) Revision: 30.03.2022

Trade name: MOTIP POWER BRAKE CLEANER 500 ML

(Contd. of page 6)

# SECTION 12: Ecological information

#### · 12.1 Toxicity

#### · Aquatic toxicity:

### Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

EC50 / 48 h | 3 mg/l (daphnia magna) EC50 / 72 h | 30-100 mg/l (algae)

- LC50 / 96 h 11.4 mg/l (fish)
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

## SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation:

Disposal must be made according to official regulations.

Disposal must be made according to official regulations.

SECTION 14:	Transport	informat	ion
-------------	-----------	----------	-----

· 14.1 UN nun	iber or ID number	
· ADR, IMDG	, IATA	UN1950

· 14.2 UN proper shipping name

· ADR 1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS

• IMDG AEROSOLS, MARINE POLLUTANT

· IATA AEROSOLS, flammable

(Contd. on page 8)

Printing date 22.02.2024 Version number 2 (replaces version 1) Revision: 30.03.2022

Trade name: MOTIP POWER BRAKE CLEANER 500 ML

(Contd. of page 7) · 14.3 Transport hazard class(es)  $\cdot ADR$ · Class 2 5F Gases. · Label 2.1 · IMDG · Class 2.1 Gases. · Label 2.1  $\cdot$  IATA · Class 2.1 Gases. · Label 2.1 · 14.4 Packing group · ADR, IMDG, IATA not regulated · 14.5 Environmental hazards: Symbol (fish and tree) · Marine pollutant: Symbol (fish and tree) · Special marking (ADR): · 14.6 Special precautions for user Warning: Gases. · Hazard identification number (Kemler code): · EMS Number: F-D,S-USW1 Protected from sources of heat. · Stowage Code SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. SG69 For AEROSOLS with a maximum capacity of 1 · Segregation Code litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class · 14.7 Maritime transport in bulk according to IMO Not applicable. instruments

(Contd. on page 9)

Printing date 22.02.2024 Version number 2 (replaces version 1) Revision: 30.03.2022

Trade name: MOTIP POWER BRAKE CLEANER 500 ML

	(Contd. of page
· Transport/Additional information:	
· <i>ADR</i>	
· Limited quantities (LQ)	IL
$\cdot$ Excepted quantities $(\widetilde{EQ})$	Code: E0
• • •	Not permitted as Excepted Quantity
· Transport category	2
· Tunnel restriction code	D
· IMDG	
· Limited quantities (LQ)	IL
$\cdot$ Excepted quantities $(\widetilde{EQ})$	Code: E0
- · · · · ·	Not permitted as Excepted Quantity
· UN ''Model Regulation'':	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY
2	HAZARDOUS

## SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Poisons Act
- · Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category

E2 Hazardous to the Aquatic Environment

P3b FLAMMABLE AEROSOLS

- Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

· Classification according to Regulation (EC) No 1272/2008

Data is based on internal technical data and technical data from suppliers.

- · Department issuing SDS: R&D legislation and regulatory advisor
- · Contact: e-mail: sds-nl@european-aerosols.com

(Contd. on page 10)

Printing date 22.02.2024 Version number 2 (replaces version 1) Revision: 30.03.2022

Trade name: MOTIP POWER BRAKE CLEANER 500 ML

(Contd. of page 9)

#### · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the

International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) DNEL: Derived No-Effect Level (UK REACH) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

Aerosol 1: Aerosols - Category 1

Press. Gas (Liq.): Gases under pressure - Liquefied gas

Flam. Liq. 2: Flammable liquids – Category 2 Skin Irrit. 2: Skin corrosion/irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

CD