

MOTIP Vaseline Spray

Ord.-no.: 000285

Technical Information



Protect your bike's rims and screw connections with MOTIP Vaseline Spray. Vaseline Spray is a universal lubricant and preservative spray with excellent adhesion. Vaseline Spray prevents clamping and protects screw connections and rims against corrosion and wear.

Quality & properties

- Water-repellent
- Excellent adhesion
- Prevents wear and sticking
- Resistant to weather influences
- Resistant to weak acids and bases
- Excellent corrosion prevention
- Misty spray pattern

Physical & chemical data

- Base: Vaseline
- Colourname: white
- Smell: Characteristic
- Surfaces: Screwed connections, Rims (Bike)
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Vapour pressure: 3500/20 bar
- Relative density: 0.89 g/ml
- Storage stability: 10 y
- Content: 400 ML

How to use

- Before use, carefully read the directions on the packaging and act accordingly.
- The aerosol should have room temperature.
- Best processing temperature 10 to 25°C.
- Before use, shake the aerosol.
- Apply the vaseline spray in a thin layer.
- Optimum lubrication is obtained after evaporation of the solvent.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labeling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

For any further technical questions call our hotline +31 (0) 561 69 44 00 from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

As of August 17, 2022 – This release replaces all eventually earlier issued versions.