

MOTIP Penetrating Oil

Technical Information



Loosen rusted parts with MOTIP Penetrating Oil. This oil has good penetrative properties, it contains graphite and MoS₂, is moisture repellent and prevents rusting.

Ord.-no: 090303, 000573, 290303

Quality & properties

- Good penetrating properties
- Contains graphite and MoS₂
- Moisture repellent
- Corrosion preventive
- Powerful jetspray
- 360° valve

Physical & chemical data

- Base: Mineral oil with graphite and MoS₂
- Colourname: no colour
- Smell: Characteristic
- Surfaces: Fastenings, Tools, Screwed connections, Rails, Gear wheels, Chains, Locks, Garden tools, Fasteners (screws, bolts and nuts), Reels
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Flash point:
 - 0 °C
 - n.a.
- Storage stability: 10 years
- Content:
 - 500 ML
 - 400 ml
 - 200 ML

How to use

- Before use, carefully read the directions on the packaging and act accordingly.
- The aerosol should have room temperature.
- Best processing temperature 10 to 25°C.
- Before use, shake the aerosol.
- Apply penetrating oil and allow it to take effect.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of July 7, 2025 – This release replaces all eventually earlier issued versions.