

MOTIP PTFE Spray

Ord.-no.: 000295, 000284

Technical Information



Lubricate all mechanical metal parts on your bike with MOTIP PTFE Spray. The spray maintains the lubricating effect of your bike chain, brake and gear levers and wheels. PTFE spray has excellent mechanical and thermal stability and prevents wear.

Quality & properties

- Outstanding mechanical and thermal stability
- Very low friction factor
- Excellent adhesion
- Prevents wear and sticking
- Resistant to weather influences
- Resistant to weak acids and bases
- Fine structure (particle size approximately 5 micrometer)
- Directed jetspray

Physical & chemical data

- Base: Mineral oil
- Colourname: transparent white
- Smell: Characteristic
- Surfaces: Chains, Derailleur, Brake cable, Brake handle, Gear wheel, Gear cable, Gear handle, Lock (Bike)
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Vapour pressure: 3500/20 bar
- Relative density: 0.88 g/ml
- Storage stability: 10 y
- Content:
 - ◊ 200 ML
 - ◊ 400 ML

How to use

- Before use, carefully read the directions on the packaging and act accordingly.
- The aerosol should have room temperature.
- Best processing temperature 5 to 30°C.
- Before use, shake the aerosol.
- Apply the PTFE spray in a thin layer.
- Optimum lubrication is obtained after evaporation of the solvent (approximately 1 minute).

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labeling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

For any further technical questions call our hotline +31 (0) 561 69 44 00 from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

As of August 17, 2022 – This release replaces all eventually earlier issued versions.